

MOORESTYLE™

Alkyd Multi-Primer

570

A pigmented, alkyd-based, multi-purpose primer for use on plaster walls and wood, and as an intermediate coat on primed metal and previously painted surfaces. It suppresses stains, has outstanding adhesion, high opacity and easy sanding. Can be used under both acrylic and enamel Wood & Metal topcoats. Formulated without lead.




Performance Features

- Multiple uses.
- Outstanding adhesion.
- Completely seals porous surfaces.
- Gives a smooth surface for a quality finish.
- Use on interior or exterior surfaces.
- Suitable for high use or commercial areas.

Colors: White. May be tinted with Moor-O-Matic colorants to light colors for additional hiding.

Toxicity: Formulated without lead or mercury.

Gloss Level: Low sheen.



Performance Guide:

Weather Resistance

Excellent when topcoated with Benjamin Moore exterior finishes.

Heat Resistance

Up to 120°C. Continuous heat will cause premature yellowing and embrittlement.

Water Resistance

Good resistance to water and condensation.

Solvent Resistance

Good resistance to aliphatic solvents and alcohols. Sensitive to aromatic hydro carbons and other strong solvents.



VOC (Volatile Organic Compounds): 570 MOORESTYLE Alkyd Multi- Primer: belongs to the category A/g SB (Primers).
EU Limit: 350g/l (2010).

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
13 – 14 m ² /L	40%	77 micrometres	31 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
3 hours to touch 16 hours to recoat	Passes 3mm mandrel	5% white spirits	Brush, Roller, Spray

Surface Preparation

Surface to be painted must be free of all loose material such as dust and peeling paint. The surface must be clean with all traces of grease, oil and dirt removed. Remove loose material by scraping and sanding. Sand glossy surfaces to a dull finish.

Plaster Walls, New or Previously Painted Wood, Primed or Previously Painted Metal: Apply one coat 570 MOORESTYLE Alkyd Multi-Primer.

Stained Surfaces: Apply one or two coats 570 MOORESTYLE Alkyd Multi-Primer.

Ferrous Metal: Must be primed. Use 568 MOORESTYLE Rust Primer, following label directions.

Application

Stir thoroughly before and during use. Apply by brush, roller or spray. Thin 5% with low odour white spirits. Do not apply when air or surface temperature is below 10°C or when the humidity is high. Drying times are longer under cool/moist conditions.

Clean Up: Clean brushes and equipment with white spirits.

Precautions - Health and Safety:

- Keep away from heat and open flame
- Repeated exposure may cause skin dryness or cracking
- Contains Methylethylketoxime. May produce an allergic reaction
- Avoid breathing vapour –use with adequate ventilation
- Skin contact: wash skin thoroughly with soap and water
- Eye contact: Treat immediately with water: Get medical attention
- If swallowed: Get medical attention without delay and display label.

Packaging and Storage

Sizes : 0,75litre, 2,5 litres

Flash Point: 44°C (Abel)

Storage: PAINTS, flammable liquid

